

Shamir Quick Reference Guide

EFFECTIVE DATE: SEPTEMBER, 2025

Click or Scan For **Glacier®** AR Portfolio and Availability



EVERYDAY			MATERIALS							MVC
			HARD RESIN 1.50	TRIVEX™ 1.53	1.56	POLYCARBONATE 1.59	1.60	1.67	1.74	
PROGRESSIVE	Shamir AUTOGRAPH INTELLIGENCE™**	POWER RANGE	-12.25 to +6.50	-13.25 to +7.00	-14.00 to +7.50	-14.75 to +8.75	-14.75 to +8.75	-16.75 to +10.00	-18.75 to +12.00	
	MIN. FH (11mm, 13mm, 15mm, 18mm)	CYLINDER	to -6.00	to -6.50	to -6.75	to -7.00	to -7.00	to -8.00	to -9.00	
	ADD Power +0.75 to +3.50	TREATMENT	C,T,P,TX,XP,D,S	C,T,P,TX,XP,N,BZ,S	B	C,T,B,P,TX,XP,D,BZ,S	C,T,P,TX	C,T,P,TX,XP,BZ,S	C,T,NPP	
	Prism up to 10.00 Diopters in each direction									
	Shamir AUTOGRAPH® III****	POWER RANGE	-12.25 to +6.00	-13.25 to +7.00	-14.00 to +6.50	-14.75 to +8.00	-15.00 to +8.00	-16.75 to +9.00	-18.75 to +12.00	
	MIN. FH (11mm, 13mm, 15mm, 18mm)	CYLINDER	to -6.00	to -6.50	to -6.75	to -7.00	to -7.00	to -8.00	to -9.00	
	ADD Power +0.75 to +4.00	TREATMENT	C,T,P,TX,XP,D,S	C,T,P,TX,XP,N,BZ,S	B	C,T,B,P,TX,XP,D,BZ,S	C,T,P,TX	C,T,P,TX,XP,BZ,S	C,T,NPP	
	Prism up to 10.00 Diopters in each direction									
	Shamir AUTOGRAPH® II+*	POWER RANGE	-12.25 to +6.00	-13.25 to +6.00	-14.00 to +6.50	-14.75 to +6.50	-15.00 to +6.00	-16.75 to +8.25	-18.75 to +12.00	
	MIN. FH (11mm, 13mm, 15mm, 18mm)	CYLINDER	to -6.00	to -6.50	to -6.75	to -7.00	to -7.00	to -8.00	to -9.00	
	ADD Power +0.75 to +4.00	TREATMENT	C,T,P,TX,XP,D,S	C,T,P,TX,XP,N,BZ,S	B	C,T,B,P,TX,XP,D,BZ,S	C,T,P,TX	C,T,P,TX,XP,BZ,S	C,T,NPP	
	Prism up to 10.00 Diopters in each direction									
	Shamir INTOUCH™	POWER RANGE	-12.25 to +6.00	-13.25 to +6.00	-14.00 to +6.00	-14.75 to +6.00	-15.00 to +6.00	-16.75 to +8.00	-18.75 to +15.50	
	MIN. FH (15mm & 18mm)	CYLINDER	to -6.00	to -6.50	to -6.75	to -7.00	to -7.00	to -8.00	to -9.00	
	ADD Power +0.75 to +3.50	TREATMENT	C,T,P,TX,XP,D,S	C,T,P,TX,XP,N,BZ,S	B	C,T,B,P,TX,XP,D,BZ,S	C,T,P,TX	C,T,P,TX,XP,BZ,S	C,T,NPP	
	Prism up to 10.00 Diopters in each direction									
	Shamir SPECTRUM+™	POWER RANGE	-12.25 to +6.00	-13.25 to +6.00	-14.00 to +6.00	-14.75 to +6.00	-15.00 to +6.00	-16.75 to +8.00	-18.75 to +11.50	
	MIN. FH (14mm, 16mm, & 18mm)	CYLINDER	to -6.00	to -6.50	to -6.75	to -7.00	to -7.00	to -8.00	to -9.00	
	ADD Power +0.75 to +3.50	TREATMENT	C,T,P,TX,XP,D,S	C,T,P,TX,XP,N,BZ	B	C,T,B,P,TX,XP,D,BZ,S	C,T,P,TX	C,T,P,TX,XP,BZ,S	C,T,NPP	
	Prism up to 10.00 Diopters in each direction									
	Shamir ELEMENT™	POWER RANGE	-7.00 to +4.00	-13.25 to +6.00	--	-10.00 to +6.00	-10.00 to +6.00	-12.50 to +8.00	--	
	MIN. FH (16mm & 19mm)	CYLINDER	to -6.00	to -6.50	--	to -7.00	to -7.00	to -8.00	--	
	ADD Power +0.75 to +3.50	TREATMENT	C,T,XP,P,S	C,T,XP,N,BZ,S	--	C,T,B,P,TX,XP,BZ,S	C,T	C,T,XP,NG,BZ,S	--	
	Prism up to 10.00 Diopters in each direction									
	Shamir GENESIS HD	POWER RANGE	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00	
	MIN. FH (16mm)	CYLINDER	to -4.00	to -4.00	to -4.00	to -4.00	to -4.00	to -4.00	to -4.00	
	ADD Power +0.75 to +3.50	TREATMENT	C,T,P,TX,XP,D,S	C,T,P,TX,XP,N,BZ	B	C,T,B,P,TX,XP,NG,D,BZ,S	C,T,P,TX	C,T,P,TX,XP,NG,BZ,S	C,T,NPP	
	Prism up to 10.00 Diopters in each direction									
SINGLE VISION	Shamir AUTOGRAPH® III - SV**	POWER RANGE	-12.00 to +7.25	-14.00 to +8.00	-14.00 to +8.50	-14.00 to +8.75	-14.00 to +8.75	-16.00 to +16.00	-20.00 to +13.50	
	Fitting Height needed Reference SV White Paper for details	CYLINDER	to -6.00	to -6.50	to -6.75	to -7.00	to -7.00	to -8.00	to -9.00	
	Prism up to 10.00 Diopters in each direction	TREATMENT	C,T,P,TX,XP,D,S	C,T,P,TX,XP,BZ,S	B	C,T,B,P,TX,XP,D,BZ,S	C,T,P,TX	C,T,P,TX,XP,BZ,S	C,T,NPP	
	Shamir RELAX™	POWER RANGE	-14.00 to +6.25	-14.00 to +8.00	-14.00 to +8.50	-14.00 to +8.75	-14.00 to +8.75	-16.75 to +16.00	-20.00 to +13.50	
	MIN. FH (14mm)	CYLINDER	to -6.00	to -6.50	to -6.75	to -7.00	to -7.00	to -8.00	to -9.00	
	ADD Power +0.50, +0.65, +0.80	TREATMENT	C,T,P,TX,XP,D,S	C,T,P,TX,XP,N,BZ,S	B	C,T,B,P,TX,XP,D,BZ,S	C,T,P,TX	C,T,P,TX,XP,BZ,S	C,T,NPP	
BIFOCAL	Shamir DUO™	POWER RANGE	-9.00 to +6.00	-13.25 to +6.00	-14.00 to +6.00	-14.75 to +6.00	-15.00 to +6.00	-16.75 to +8.00	-18.75 to +12.00	
	MIN. FH (15mm)	CYLINDER	to -6.00	to -6.50	to -6.75	to -7.00	to -7.00	to -8.00	to -9.00	
	ADD Power +0.75 to +4.00	TREATMENT	C,T,P,TX,XP,D,S	C,T,P,TX,XP,N,BZ,S	B	C,T,B,P,TX,XP,D,BZ,S	C,T,P,TX	C,T,P,TX,XP,BZ,S	C,T,NPP	
	Prism up to 10.00 Diopters in each direction									

LEGEND

- C CLEAR
- T TRANSITIONS® GEN S™
- TX TRANSITIONS® XTRACTIVE® New Generation
- TXP TRANSITIONS® XTRACTIVE® Polarized™
- B BLUTECH (INDOOR & OUTDOOR)
- P POLARIZED
- D DRIVEWEAR
- BZ BLUE ZERO™
- S SUNSYNC®
- NPP NuPolar® Polarized

Please confirm with your Shamir distributing lab Rx range and index availability as it may differ from above.

Shamir Glacier® AR Coatings, Crizal AR Coating, Zeiss AR Coating, Hoya AR Coating, Unity AR Coating and iCoat AR Coating applicable with correct blank.
All Shamir products are available with your lab's in-house AR Coatings. Please check with your lab to determine which specific manufacturer's AR coating is available with the Shamir lens and material that you are ordering, as a manufacturer may offer more than one AR coating.
Visit VSP website for current VSP codes.

* Preferred Treatment

* Utilizes As-Worn Technology™ (SEE PRODUCT FLYER FOR MORE INFORMATION)

** Utilizes As-Worn Quadro® and As-Worn Technology™ (SEE PRODUCT FLYER FOR MORE INFORMATION)

*** Unique to Computer™ and Workspace™ Lenses

**** Utilizes As-Worn POV™

⚠ **WARNING:** Polycarbonate lenses can expose you to chemicals including Bisphenol A (BPA) and 1,74 index lenses can expose you to Methimazole, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to: www.P65Warnings.ca.gov.

SHA-ORG-090525



shamir
877.514.8330
shamirlens.com

Shamir Quick Reference Guide

EFFECTIVE DATE: SEPTEMBER, 2025

Click or Scan For **Glacier®** AR Portfolio and Availability



WORK

			MATERIALS							MVC
			HARD RESIN 1.50	TRIVEX™ 1.53	1.56	POLYCARBONATE 1.59	1.60	1.67	1.74	
PROGRESSIVE	Shamir COMPUTER™ MIN. FH (14mm LOWER/10MM UPPER) ADD power +0.75 to +3.50 Dynamic Reduction -0.75 to -2.00 Prism up to 10.00 Diopters in each direction	TOTAL NEAR POWER RANGE***	-6.00 to +6.00	-6.00 to +8.00	-6.00 to +8.00	-6.00 to +8.00	-6.00 to +8.00	-8.50 to +8.75	--	
		CYLINDER	to -6.00	to -6.50	to -6.75	to -7.00	to -7.00	to -8.00	--	
		TREATMENT	C,T,P,TX,TXP,S	C,T,P,TX,TXP,N,BZ,S	B	C,T,P,TX,TXP,B,BZ,S	C,T,P,TX	C,T,P,TX,TXP,BZ,S	--	
	Shamir WORKSPACE™ MIN. FH (14mm LOWER/10MM UPPER) ADD power +0.75 to +3.50 Dynamic Reduction -0.75 to -2.50 Prism up to 10.00 Diopters in each direction	TOTAL NEAR POWER RANGE***	-6.00 to +6.00	-6.00 to +8.00	-6.00 to +8.00	-6.00 to +8.00	-6.00 to +8.00	-8.50 to +8.75	--	
		CYLINDER	to -6.00	to -6.50	to -6.75	to -7.00	to -7.00	to -8.00	--	
		TREATMENT	C,T,P,TX,TXP,S	C,T,P,TX,TXP,N,BZ,S	B	C,T,P,TX,TXP,B,BZ,S	C,T,P,TX	C,T,P,TX,TXP,BZ,S	--	

PLAY GREAT FOR WRAP FRAMES

			MATERIALS							MVC
			HARD RESIN 1.50	TRIVEX™ 1.53	1.56	POLYCARBONATE 1.59	1.60	1.67	1.74	
PROGRESSIVE	Shamir ATTITUDE® III - FASHION** MIN. FH (15mm, & 18mm) ADD Power +0.75 to +3.50 Prism up to 10.00 Diopters in each direction	POWER RANGE	-6.50 to +5.25	-6.50 to +6.00	-6.50 to +6.00	-6.50 to +6.00	-6.50 to +6.00	-6.50 to +6.00	--	
		CYLINDER	to -6.00	to -6.50	to -6.75	to -7.00	to -7.00	to -8.00	--	
		TREATMENT	C,T,P,TX,TXP,D,S	C,T,P,TX,TXP,N,BZ,S	B	C,T,B,P,TX,TXP,D,BZ,S	C,T,P,TX	C,T,P,TX,TXP,BZ,S	--	
	Shamir ATTITUDE® III - SPORT** MIN. FH (18mm) ADD Power +0.75 to +3.50 Prism up to 10.00 Diopters in each direction	POWER RANGE	-6.50 to +5.25	-6.50 to +6.00	-6.50 to +6.00	-6.50 to +6.00	-6.50 to +6.00	-6.50 to +6.00	--	
		CYLINDER	to -6.00	to -6.50	to -6.75	to -7.00	to -7.00	to -8.00	--	
		TREATMENT	C,T,P,TX,TXP,D,S	C,T,P,TX,TXP,N,BZ,S	B	C,T,B,P,TX,TXP,D,BZ,S	C,T,P,TX	C,T,P,TX,TXP,BZ,S	--	
SINGLE VISION	Shamir GOLF™* MIN. FH (19mm) ADD Power +1.00 to +3.50 Prism up to 10.00 Diopters in each direction	POWER RANGE	--	-5.00 to +4.00	-5.50 to +5.25	-6.00 to +5.25	-6.00 to +5.25	--	--	
		CYLINDER	--	to -6.50	to -6.75	to -7.00	to -7.00	--	--	
		TREATMENT	--	C,T,P,TX,TXP,N,BZ,S	B	C,T,B,P,TX,TXP,D,BZ,S	C,T,P,TX	--	--	
	Shamir ATTITUDE® III - SV** Fitting height needed Reference SV White Paper for details Prism up to 10.00 Diopters in each direction	POWER RANGE	-6.50 to +6.00	-6.50 to +6.00	-6.50 to +6.00	-6.50 to +6.00	-6.50 to +6.00	-6.50 to +6.00	--	
		CYLINDER	to -6.00	to -6.50	to -6.75	to -7.00	to -7.00	to -8.00	--	
		TREATMENT	C,T,P,TX,TXP,D,S	C,T,P,TX,TXP,N,BZ,S	B	C,T,B,P,TX,TXP,D,BZ,S	C,T,P,TX	C,T,P,TX,TXP,BZ,S	--	

DRIVE GREAT FOR WRAP FRAMES

			MATERIALS							MVC
			HARD RESIN 1.50	TRIVEX™ 1.53	1.56	POLYCARBONATE 1.59	1.60	1.67	1.74	
PROGRESSIVE	Driver Intelligence™ SUN**** MIN. FH (18MM) ADD power +0.75 to +3.50 Prism up to 10.00 Diopters per quadrant	POWER RANGE	--	-10.00 to +6.00	--	-14.75 to +6.00	--	-16.75 to +6.00	--	
		MAX CYLINDER	--	-6.50	--	-7.00	--	-8.00	--	
		TREATMENT	--	C,P ¹ ,BZ,T,TX	--	C,P ¹ ,BZ,T,TX	--	C,P ¹ ,BZ,T,TX	--	
	Driver Intelligence™ MOON**** MIN. FH (18MM) ADD power +0.75 to +3.50 Prism up to 10.00 Diopters in each direction	POWER RANGE	--	-10.00 to +6.00	--	-14.75 to +6.00	--	-16.75 to +6.00	--	
		MAX CYLINDER	--	-6.50	--	-7.00	--	-8.00	--	
		TREATMENT	--	C ¹ ,P,BZ,T,TX	--	C ¹ ,P,BZ,T,TX	--	C ¹ ,P,BZ,T,TX	--	
SINGLE VISION	Driver Intelligence™ SUN - SV**** Fitting height needed Reference SV White Paper for details Prism up to 10.00 Diopters in each direction	POWER RANGE	--	-12.00 to +6.00	--	-14.00 to +6.00	--	-16.00 to +6.00	--	
		MAX CYLINDER	--	-6.50	--	-7.00	--	-8.00	--	
		TREATMENT	--	C,P ¹ ,BZ,T,TX	--	C,P ¹ ,BZ,T,TX	--	C,P ¹ ,BZ,T,TX	--	
	Driver Intelligence™ MOON - SV**** Fitting height needed Reference SV White Paper for details Prism up to 10.00 Diopters in each direction	POWER RANGE	--	-12.00 to +6.00	--	-14.00 to +6.00	--	-16.00 to +6.00	--	
		MAX CYLINDER	--	-6.50	--	-7.00	--	-8.00	--	
		TREATMENT	--	C ¹ ,P,BZ,T,TX	--	C ¹ ,P,BZ,T,TX	--	C ¹ ,P,BZ,T,TX	--	

LEGEND

C CLEAR
T TRANSITIONS® GEN S™
TX TRANSITIONS® XTRACTIVE® New Generation
TXP TRANSITIONS® XTRACTIVE® Polarized™
B BLUTECH (INDOOR & OUTDOOR)
P POLARIZED
D DRIVEWEAR
BZ BLUE ZERO™
S SUNSYNC®
NPP NuPolar® Polarized

Please confirm with your Shamir distributing lab Rx range and index availability as it may differ from above.

Shamir Glacier® AR Coatings, Crizal AR Coating, Zeiss AR Coating, Hoya AR Coating, Unity AR Coating and iCoat AR Coating applicable with correct blank.
 All Shamir products are available with your lab's in-house AR Coatings. Please check with your lab to determine which specific manufacturer's AR coating is available with the Shamir lens and material that you are ordering, as a manufacturer may offer more than one AR coating.
 Visit VSP website for current VSP codes.

¹ Preferred Treatment

* Utilizes As-Worn Technology™ (SEE PRODUCT FLYER FOR MORE INFORMATION)

** Utilizes As-Worn Quadro® and As-Worn Technology™ (SEE PRODUCT FLYER FOR MORE INFORMATION)

*** Unique to Computer™ and WorkSpace™ Lenses

**** Utilizes As-Worn POV™

⚠ WARNING: Polycarbonate lenses can expose you to chemicals including Bisphenol A (BPA) and 1,74 index lenses can expose you to Methimazole, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to: www.P65Warnings.ca.gov.

SHA-ORG-090525


shamir
 877.514.8330
shamirlens.com